



Gas Carrier SYN ZUBE

Type of Ship	LPG Carrier
Year	2009
Flag	Italian
Builder	Cantieri Navali, Pesaro
Class Society	RINA/BV
Class Notation	C+ Liquefied gas carrier - unrestricted navigation
Additional Notation	+AUT-PORT; +AUT-UMS; +AVM-APS; CLEAN SEA; INWATERSURVEY; MON-SHAFT
IMO Number	9346940

GENERAL INFO

Type of Ship	LPG Carrier
Year	2009
Flag	Italian
Builder	
Cantieri Navali, Pesaro	
Class Society	RINA/BV
Class Notation	
C+ Liquefied gas carrier - unrestricted navigation	
Additional Notation	
+AUT-PORT; +AUT-UMS; +AVM-APS; CLEAN SEA; INWATERSURVEY; MON-SHAFT	
IMO Number	9346940

MAIN DATA

LOA	95.5	mt
LBP	86.35	mt
Breadth	15.5	mt
Depth Mould	8	mt
K.T.M.	31.00	mt
Air Draught (normal ballast)		
26		
Summer draught	6.5	mt
Corresponding DWT	4026	- MT
Loaded Displacement	2353	- MT
Light Displacement	6379	- MT
TPC on Summer Draught	12.3	- MT
Int. GRT	3827	
Int. NRT	1148	
Suez GRT	4176	
Suez NRT	3106	

BUILT

Shipyard	
Cantieri Navali, Pesaro	
Delivery Date	17/11/2009

CLASS

RINA/BV	100 A1-1/NAV. I.L CST
---------	-----------------------

MAIN ENGINE

Type	MAN B&W
Power	2380 - Kw
Fuel Grade	IFO 180

AUXILIARY ENGINE

Number	3
Type	VOLVO PENTA TAMD 165 A
Power	400 - Kw
Fuel Grade	Gasoil

SHAFT GEN.

Shaft Gen.	660 - Kw
------------	----------

BOW THRUSTER

Type	Brumvoll
Power	300 - Kw

PROPELLER

Type	Pitch
------	-------

BUNKER

Capacity FO 100%	313	cbm
Capacity GO 100%	114	cbm

BALLAST

Capacity	1586	cbm
Number of Pumps	3	
Pumping Capacity	250	- cbm/hr

LOADING

Capacity cbm/hr	max 500	- cbm/hr
-----------------	---------	----------

DISCHARGING

Capacity cbm/hr	max 400	- cbm/hr
-----------------	---------	----------

FRESH WATER

Capacity of Tanks	80	- MT
Generated per Day	7	- MT

CROSSOVER

Distance Liquid 1 from bow	52.16
Distance Liquid 1 from stern	43.04
Distance Vapour 1 from bow	53.38
Distance Vapour 1 from stern	41.81
Distance Liquid 2 from bow	55.86
Distance Liquid 2 from stern	39.35
Distance Vapour 2 from bow	54.61
Distance Vapour 2 from stern	40.58

DISTANCE MANIFOLD

From Grating	1.1	mt
From Ship's Rail	1.3	mt
From Main Deck	4.8	mt
Abow W/L SDWT	5.2	mt
Abow W/L Ballast	6.9	mt

PARALLEL BODY LENGHT

At Summer Draught	54	mt
At Ballast Draught	45	mt

CARGO TANKS

Number	2
Type	Tyoe C Cylindric
Max tank press IMO	8 - barg
Max tank press USCG	5 - barg

Max Vacuum	-0.25 - barg
Min. Temp.	-48 - Å°C
Max Density/S.G.	0.97

TANKS CAPACITY

100%	4.007,1 cbm
TK1	1.955,2 cbm
TK2	2.051,9 cbm

CARGO SEGREGATION

Number of Grades	2
List of Segregation	1-2

CARGO PUMPS

Type	Deepwell Swanehey
Number	2
Capacity	250 - cbm/hr
M.L.C.	120
Max Density/S.G.	0.97

BOOSTER PUMP

Number	1
Capacity	250 - cbm/hr
M.L.C.	120
Max Density/S.G.	0.68

CARGO HEATER

Number	1
Heating Medium	sea water
Capacity (sea water 15Å??Å°C)	370 - cbm/hr

CARGO COMPRESSORS

Number	2
Type	Sulzer 2K 140-2F/S/i

CRANE

Number (Hoisting Hoses)	
Number (Hoisting Hoses)	
SWL	3 - MT